

a mysterious cat has 18 half-lives.

Table of contents

- [Tikiwiki on SuSE-based Linux Systems](#)
 - [Anon Checkout on sf.net](#)
 - [spec.file for tikiwiki 1.9.x on SuSE-based Linux Systems](#)

PlayGround

Tikiwiki on SuSE-based Linux Systems

This section is a start for a Page "Installing tikiwiki on SuSE-based Linux Systems".

Anon Checkout on sf.net

□□□□□□

```
#!/bin/bash # far from being usable PN=${0##*/} export
CVSROOT="pserver:anonymous@cvs.sourceforge.net:/cvsroot/tikiwiki"; BASE=`pwd`
LOGDIR=${BASE}/logs tikiversions="1.10:tikiwiki 1.9:BRANCH-1-9"; cvsmode=${1:-
update} cvsclean() { find . -type d -name "CVS" -exec rm -rf {} &gt; /dev/null 2&gt;&
; \; find . -type f -exec md5sum {} \; &gt; ${LOGDIR}/md5sums.${jav%%:*} } bckold() { local jav local
iav printf "Backup old Data ..." [ ! -d old ] & & mkdir old for iav
in ${tikiversions} ; do jav=${iav%%:*} if [ -d ${jav} ]; then if [ "yes" =
"yes" ]; then tar cf - ${jav} | ( cd old ; tar xf - ) rm -rf ${jav} mkdir ${jav} fi else [
"no" = "no" ] & & cvsmode=co mkdir ${BASE}/${jav} fi
done } cvslogin() { cvs login rc=$? return $rc } checkout() { local a=${1:-`pwd`} local jav printf
"Checkout" for jav in ${tikiversions} ; do printf "Checkout ${jav%%:*}" cd ${BASE}/${jav%%:*} echo ${jav##*:} | grep -i BRANCH
&gt;/dev/null 2&gt;& ; 1 if [ $? -eq 0 ]; then cvsmode="<code>${cvsmode} -r" fi cvs -z3
${cvsmode} ${jav##*:} tikiwiki &gt; ${LOGDIR}/logfile.${jav%%:*} [ $? -eq 0 ] & &
cvs clean done } #main() [ "update" = "update" ] & &
removedirs=no || removedirs=yes bckold cvslogin checkout ${BASE}
```

spec.file for tikiwiki 1.9.x on SuSE-based Linux Systems

□□□□□□

```
# tikiwiki.spec # version: 0.0.1 %define is_suse %[ -f /etc/SuSE-release ] & & echo 1 || echo 0
) %if %{is_suse} == 1 %define SUSEVER `(awk 'NR==1 {sub(/\./,""); print $NF}' /etc/SuSE-release) %endif %if %{SUSEVER} < 30 %define is_sles 1 %define _mydist
sles%{SUSEVER} %else %define is_sles 0 %define _mydist suse%{SUSEVER} %endif %define name
tikiwiki %define sname tiki %define version 1.9.2 %define release 2%{_mydist} %define webroot
/srv/www %define wwwowner wwwrun %define wwwgroup www %define usesetupsh 0 Summary: A
PHP based CMS/Groupware with a full WIKI environment Name: %{name} Version: %{version}
Release: %{release} Source:
http://prdownloads.sourceforge.net/{name}/{name}-{version}.tar.gz License: LGPL Packager:
Frank Hollmann &lt;frank.hollmann@lst.bayern.de> Group: Applications/Internet URL:
http://www.tiki.org Requires: webserver php mysql php-mysql BuildArch: noarch BuildRoot:
%{_tmppath}/{name}-root Provides: tikiwiki %description Tikiwiki is an open source (LGPL), php-
```

```
based, CMS/Groupware web application with a full wiki environment. %prep %setup -q %build %install
install -d -m0750 -o root -g root -p %buildroot%webroot install -d -m0750 -o root -g root -p
%buildroot%webroot/%sname-%version # cleanup cvs tree find . -type d -name *CVS* | xargs
-- rm -rf &gt;/dev/null 2&gt;&1 find . -name &quot;.cvsignore&quot; -exec rm -f {} \; rm -rf
templates_c/* rm -f modules/cache/*.cache # copy the files tar cf - . | ( cd
%buildroot%webroot/%sname-%version ; tar xf - ) %clean if [ -n %buildroot -a !
%buildroot = &quot;/&quot; ]; then rm -rf %buildroot fi %pre # for SuSE only. %if %is_suse ==
0 printf &quot;%s\n&quot; &quot;This is a package for SuSE Distributions. Sorry for the
inconvenience&quot; exit 1 %endif %post cd %webroot/%sname-%version if [ %usesetupsh -
eq 0 ]; then if [ -f fixperms.sh ]; then sh ./fixperms.sh fix %wwwowner %wwwgroup fi else if [ -f
setup.sh ]; then chmod 700 setup.sh sh ./setup.sh %wwwowner %wwwgroup fi fi %preun rm -rf
templates_c/* rm -f modules/cache/*.cache %files %defattr(-, %wwwowner, %wwwgroup) %doc
README INSTALL fixperms.sh setup.sh %webroot/%sname-%version/* %changelog * Tue Oct
04 2005 Frank Hollmann <abholmarkt@h00.net>; 1.9.2-1 - cvs tree used - first package for SUSE
```